Page: 1/11

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 05, 2018 Revision: October 05, 2018

1 Identification

Product identifier

· Trade name: PROseal

PROseal Spray **FIBERseal**

- · Other means of identification: No other identifiers
- · Recommended use and restriction on use
- · Recommended use: Sealant
- · Restrictions on use: No relevant information available.
- Details of the supplier of the Safety Data Sheet
- · Manufacturer/Supplier:

Ductmate Industries, Inc.

210 5th St.

Charleroi, PA 15022 Phone: 800-990-8459



Emergency telephone number:

ChemTel Inc.

(800)255-3924 (North America) +1 (813)248-0585 (International)

2 Hazard(s) identification

· Classification of the substance or mixture

The product is not classified as hazardous according to the Globally Harmonized System (GHS).

- · Label elements
- · GHS label elements Not regulated.
- · Hazard pictograms: Not regulated.
- · Signal word: Not regulated.
- · Hazard statements: Not regulated.
- Other hazards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Componen	· Components:			
1317-65-3	Limestone		10-40%	
14807-96-6	Talc (Mg3H2(SiO3)4)		10-40%	
	Magnesite		<10%	
107-21-1	Ethylene glycol	STOT RE 2, H373 Acute Tox. 4, H302	<5%	
68412-54-4	Nonylphenol, branched, ethoxylated	Eye Irrit. 2B, H320	<1%	
14808-60-7	Quartz		<1%	

Additional information:

For the wording of the listed Hazard Statements, refer to section 16.

Non-classification as a carcinogen is based on non-inhalable form of product. IARC listings for quartz note

(Cont'd. on page 2)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 05, 2018 Revision: October 05, 2018

Trade name: PROseal

PROseal Spray FIBERseal

(Cont'd. of page 1)

that the substance must be respirable.

4 First-aid measures

- Description of first aid measures
- After inhalation:

Respiration of particulates is unlikely during normal usage.

Supply fresh air and to be sure to call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eve contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

· Most important symptoms and effects, both acute and delayed:

Headache

Dizziness

Nausea

· Indication of any immediate medical attention and special treatment needed: Treat symptomatically.

5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents:

The product is not flammable.

Use fire fighting measures that suit the environment.

- · For safety reasons unsuitable extinguishing agents: None.
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Use personal protective equipment as required.

Environmental precautions

Do not allow to enter sewers/ surface or ground water.

(Cont'd. on page 3)

Page: 3/11

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 05, 2018 Revision: October 05, 2018

Trade name: PROseal

PROseal Spray FIBERseal

(Cont'd. of page 2)

Inform respective authorities in case of seepage into water course or sewage system.

· Methods and material for containment and cleaning up

Towel or mop up material and collect in a suitable container.

For larger spills, add sawdust, chalk or other inert binding material, then sweep up and discard.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- Handling
- Precautions for safe handling:

Keep away from heat and direct sunlight.

Use only in well ventilated areas.

Avoid contact with the eyes and skin.

- Information about protection against explosions and fires: No special measures required.
- Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and receptacles:

Store in cool, dry conditions in well sealed receptacles.

Information about storage in one common storage facility:

Store away from oxidizing agents.

Store away from foodstuffs.

- Further information about storage conditions: Protect from frost.
- · Specific end use(s) No relevant information available.

8 Exposure controls/personal protection

· Control parameters

Control parameters		
· Components	with limit values that require monitoring at the workplace:	
1317-65-3 Lir	mestone	
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction	
REL (USA) Long-term value: 10* 5** mg/m³ *total dust **respirable fraction		
TLV (USA)	TLV withdrawn	
14807-96-6 Talc (Mg3H2(SiO3)4)		
PEL (USA)	Long-term value: 20 mppcf ppm (containing <1% Quartz)	
REL (USA)	Long-term value: 2* mg/m³ *respirable dust; and <1% Quartz	
TLV (USA)	Long-term value: 2* mg/m³ *as respirable fraction; E	
	(Cont'd. on page 4	

Page: 4/11

Safety Data Sheet acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 05, 2018 Revision: October 05, 2018

Trade name: PROseal

PROseal Spray FIBERseal .

		(Cont'd. of page 3)
EL (Canada)	Long-term value: 2 *0.1 f/cc mg/m³ resp. *if contains asbestos : ACGIH A1, IARC 1	
EV (Canada)	Long-term value: 2* mg/m³, 2 f/cc ppm *respirable	
LMPE (Mexico)	Long-term value: 2* mg/m³ A4, *fracción respirable	
546-93-0 Magn	•	
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction	
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction	
TLV (USA)	TLV withdrawn	
EL (Canada)	Long-term value: 10* 3** mg/m³ *total dust, **respirable fraction	
EV (Canada)	Long-term value: 10 mg/m³ total dust	
LMPE (Mexico)	Short-term value: 20 mg/m³ Long-term value: 10 mg/m³ (e)	
107-21-1 Ethyle	ene glycol	
TLV (USA)	Short-term value: 10** mg/m³, 50* ppm Long-term value: 25* ppm *vapor fraction:**inh. fraction, aerosol only	
WEEL (USA)	Long-term value: 10 mg/m³	
EL (Canada)	Short-term value: 20** mg/m³ Long-term value: 10** mg/m³ Ceiling limit value: 100* mg/m³, 50*** ppm *Aerosol; **Particulate; ***Vapour	
EV (Canada)	Ceiling limit value: 100 mg/m³	
LMPE (Mexico)	Ceiling limit value: 100* mg/m³ A4, *solo aerosol	
14808-60-7 Qua	artz	
PEL (USA)	Long-term value: 0.05* mg/m³ *resp. dust; 30mg/m3/%SiO2+2	
REL (USA)	Long-term value: 0.05* mg/m³ *respirable dust; See Pocket Guide App. A	
TLV (USA)	Long-term value: 0.025* mg/m³ *as respirable fraction	
EL (Canada)	Long-term value: 0.025 mg/m³ ACGIH A2; IARC 1	
EV (Canada)	Long-term value: 0.10* mg/m³ *respirable fraction	
LMPE (Mexico)	Long-term value: 0.025* mg/m³	(Cont'd. on page 5)
		(Cont u. on page 3)

Page: 5/11

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 05, 2018 Revision: October 05, 2018

Trade name: PROseal

PROseal Spray FIBERseal

(Cont'd. of page 4)

A2, *fracción respirable

• Exposure controls

· General protective and hygienic measures:

Avoid close or long term contact with the skin.

Avoid contact with the eyes.

Keep away from foodstuffs, beverages and feed.

Do not breathe dust/fume/gas/mist/vapors/spray.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

- · Engineering controls: No relevant information available.
- Breathing equipment:

Not necessary if room is well-ventilated.

Use respiratory protection when grinding or cutting material.

· Protection of hands:

Gloves are advised for repeated or prolonged contact.

Wear protective gloves to handle contents of damaged or leaking units.

- Eye protection: Follow relevant national guidelines concerning the use of protective eyewear.
- Body protection: Protective work clothing
- Limitation and supervision of exposure into the environment

Avoid release to the environment.

· Risk management measures No relevant information available.

9 Physical and chemical properties

Appearance:		
Form:	Liquid	
Color:	According to product specification	
Odor:	Mild	
Odor threshold:	Not determined.	
pH-value:	Not applicable.	
Melting point/Melting range:	Not determined.	
Boiling point/Boiling range:	Not determined.	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not determined.	
Auto-ignition temperature:	Not determined.	
Decomposition temperature:	Not determined.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits		
Lower:	Not determined.	
Upper:	Not determined.	

Page: 6/11

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 05, 2018 Revision: October 05, 2018

Trade name: PROseal

PROseal Spray FIBERseal

		(Cont'd. of page
Oxidizing properties:	Non-oxidizing.	
· Vapor pressure:	Not applicable.	
· Density:		
Relative density:	Not determined.	
Vapor density:	Not applicable.	
Evaporation rate:	Not applicable.	
Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octanol/v	vater): Not determined.	
· Viscosity		
Dynamic:	Not applicable.	
Kinematic:	Not applicable.	
Other information	No relevant information available.	

10 Stability and reactivity

- · Reactivity: No relevant information available.
- Chemical stability:
- · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- · Possibility of hazardous reactions Reacts with strong oxidizing agents.
- · Conditions to avoid Excessive heat.
- · Incompatible materials Oxidizers
- · Hazardous decomposition products

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

11 Toxicological information

- Information on toxicological effects
- Acute toxicity: Based on available data, the classification criteria are not met.
- LD/LC50 values that are relevant for classification: None.
- · Primary irritant effect:
- On the skin: Based on available data, the classification criteria are not met.
- · On the eye: Based on available data, the classification criteria are not met.
- · Sensitization: Based on available data, the classification criteria are not met.
- IARC (International Agency for Research on Cancer):

Present in trace quantities: all except quartz.

14808-60-7	Quartz	1
111-42-2	2,2'-iminodiethanol	2B
123-91-1	1,4-dioxane	2B
	(Cont'd on n	age 7)

Page: 7/11

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 05, 2018 Revision: October 05, 2018

Trade name: PROseal

PROseal Spray FIBERseal

l			(Cont'd. of pa	age 6)
l	75-07-0	acetaldehyde		2B
	75-21-8	Ethylene oxide		1
	140-88-5	ethyl acrylate		2B

NTP (National Toxicology Program):

Present in trace quantities: all except quartz.

14808-60-7	Quartz	K
123-91-1	1,4-dioxane	R
75-07-0	acetaldehyde	R
75-21-8	Ethylene oxide	K

OSHA-Ca (Occupational Safety & Health Administration):

Present in trace quantities.

75-21-8 Ethylene oxide

· Probable route(s) of exposure:

Ingestion.

Eye contact.

Skin contact.

- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity:

Contains known or suspect carcinogens when inhaled. Product is in non-inhalable form and is nonclassifiable as a carcinogen.

- · Reproductive toxicity: Based on available data, the classification criteria are not met.
- · STOT-single exposure: Based on available data, the classification criteria are not met.
- · STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · Aspiration hazard: Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- · Aquatic toxicity

Toxic to aquatic life with long lasting effects.

68412-54-4 Nonylphenol, branched, ethoxylated

LC50 0.136 mg/l (pimephales promelas)

EC50 0.148 mg/l (daphnia)

- Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- Mobility in soil: No relevant information available.
- · Additional ecological information
- · General notes:

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

Avoid release to the environment.

- Results of PBT and vPvB assessment
- · **PBT**: Not applicable.

(Cont'd. on page 8)

Page: 8/11

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 05, 2018 Revision: October 05, 2018

Trade name: PROseal

PROseal Spray FIBERseal

(Cont'd. of page 7)

- · **vPvB:** Not applicable.
- Other adverse effects No relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

- Uncleaned packagings
- · **Recommendation:** Disposal must be made according to official regulations.

Transport information	
· UN-Number · DOT, ADR, IMDG, IATA	UN3082
UN proper shipping name DOT	Environmentally hazardous substances, liquid, n.o (Nonylphenol, branched, ethoxylated)
· ADR, IMDG · IATA	ENVÍRONMÉNTALLY HAZARDOÚS SUBSTANC LIQUID, N.O.S. (Nonylphenol, branched, ethoxylated Environmentally hazardous substance, liquid, n.o (Nonylphenol, branched, ethoxylated)
Transport hazard class(es)	
· DOT, IMDG, IATA	
**	
· Class · Label	9 9
· ADR	
₩	
Class	9 (M6)
Label	9 `
· Packing group	

Page: 9/11

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 05, 2018 Revision: October 05, 2018

Trade name: PROseal

PROseal Spray FIBERseal

	(Cont'd. of page 8)
· DOT, ADR, IMDG, IATA	III
Environmental hazards Marine pollutant:	Product contains environmentally hazardous substances: Nonylphenol, branched, ethoxylated No Yes (DOT)
	Symbol (fish and tree)
Special precautions for user	Warning: Miscellaneous dangerous substances and articles
· Danger code (Kemler): · EMS Number:	90 F-A,S-F
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.
· Transport/Additional information:	Not regulated when carried in single or combination packaging containing a net quantity of 5 L or less for liquids or 5 kg or less for solids per the following: ADR: SP 375 IMDG: 2.10.2.7 IATA: special provision A197
· DOT	
Remarks:	Transport labeling is not required for non-bulk single package shipments by motor vehicle, rail car or aircraft. Bulk packaging consists of a maximum capacity of greater than 450L (119 gallons) for a liquid and a maximum net mass greater than 400kg (882 pounds) for a solid.

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- · Section 302 (extremely hazardous substances):

None of the ingredients are listed.

Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

107-21-1 Ethylene glycol

· TSCA (Toxic Substances Control Act)

All ingredients are listed or exempt.

· Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

(Cont'd. on page 10)

Page: 10/11

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 05, 2018 Revision: October 05, 2018

Trade name: PROseal

PROseal Spray FIBERseal

	(Cont'd. of page 9
75-07-0 acetaldehyde	10000
75-21-8 Ethylene oxide	10000
· Proposition 65 (California)	
Chemicals known to cause cancer:	
Present in trace quantities: all except quartz and talc.	
14807-96-6 Talc (Mg3H2(SiO3)4)	
14808-60-7 Quartz	
111-42-2 2,2'-iminodiethanol	
123-91-1 1,4-dioxane	
75-07-0 acetaldehyde	
75-21-8 Ethylene oxide	
140-88-5 ethyl acrylate	
· Chemicals known to cause developmental toxicity for females:	
Present in trace quantities.	
75-21-8 Ethylene oxide	
Chemicals known to cause developmental toxicity for males:	
Present in trace quantities.	
75-21-8 Ethylene oxide	
Chemicals known to cause developmental toxicity:	
Present in trace quantities: ethylene oxide.	
107-21-1 Ethylene glycol	
75-21-8 Ethylene oxide	
· EPA (Environmental Protection Agency):	
None of the ingredients are listed.	
IARC (International Agency for Research on Cancer):	
Present in trace quantities: all except quartz.	T.
14808-60-7 Quartz	1
111-42-2 2,2'-iminodiethanol	2B
123-91-1 1,4-dioxane	2B
75-07-0 acetaldehyde	2B
75-21-8 Ethylene oxide	1
140-88-5 ethyl acrylate	2B
· Canadian Domestic Substances List (DSL) (Substances not listed.):	
All ingredients are listed or exempt.	

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Abbreviations and acronyms:

(Cont'd. on page 11)

Page: 11/11

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: October 05, 2018 Revision: October 05, 2018

Trade name: PROseal

PROseal Spray FIBERseal

(Cont'd. of page 10)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistant, Bio-accumulable, Toxic

vPvB: very Persistent and very Bioaccumulative

OSHA: Occupational Safety & Health Administration

Acute Tox. 4: Acute toxicity - Category 4

Eye Irrit. 2B: Serious eye damage/eye irritation - Category 2B

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com